

32 ZONE FIRE ALARM CONTROL PANEL

MODEL NO-(C-132Z)



This is microcontroller based conventional fire alarm panel which monitor 32 zone status and display the same in LCD & LED.

In case of event (Fire/Fault/Short) it will indicate the respective Zones and also perform the required action like activating the common/ Zone Wise hooter of the panel.

This Is Latest Technology Fire Alarm Panel Which is designed to be used for Residential, commercial, pharma, hotels & industrial Buildings.

Features and Benefits :

- As Per IS-15908:2011 Standard.
- 16x2 Dot Matrix LCD Display.
- Zone Wise Fire/Fault LED Indication.
- Short Circuit/Overload Protection.
- Potential Free Contact Facility.
- Inbuilt Battery Charger & Battery Space. (2 Battery 12V 7Ah)
- Auto Dialler Integration Facility.
- Zone Healthy Indication.
- RS 485 Communication for Repeater Panel.

+91-8527498960, 8527498961, 8527498962

sales@agniprotection.com, support@agniprotectionindia.com

www.agniprotection.com



An ISO 9001-2008 Certified Co.
AGNI PROTECTION PVT. LTD.
DATASHEET

- Compatible With all Make Conventional Sensors.
- Relay Output for Actuators, For Fire & Fault.
- Lamp Test Facility.
- User Friendly Key pad for easy panel operation.
- Zone Isolation Facility with Zone Voltage Cutoff.
- Low Battery Visual Warning.
- Evacuate Switch for Emergency.
- Zone Name Editing Facility.

Technical Specifications :

Mains Voltage	220~230V AC
Frequency	50~60 Hz
Power Consumption	5 Watt/45 Watt (Normal/Fire)
Operating Voltage	24 V DC
Detection O/P Supply	24 V DC
Hooter O/P Supply	24 V DC
No of Relays	36

Initiating Device Circuits (Zone Circuit): -

All Zones are Class B wiring

Normal Operating Voltage	16-24 V DC
Alarm Current	15-30mA
Short Circuit Current	100 mA
Maximum Zone Resistance	220 ohms
End of Line	4.7k
Standby Current	200 mA

ENVIRONMENTAL INFORMATION:

Operating Temperature	0 °C to + 65 °C
Operating Humidity	5 to 95% Relative Humidity (non- condensing)

MECHANICAL SPECIFICATION:

Cabinet Type	CRCA With Powder Coated Finish
Colour	Off White/Black/Red
Knock- Out	20mm
Dimension (WXHxD)	660 X410X180 mm
Weight without Batter	16 Kg (No Battery Fitted)

+91-8527498960, 8527498961, 8527498962

sales@agniprotection.com, support@agniprotectionindia.com

www.agniprotection.com



An ISO 9001-2008 Certified Co.
AGNI PROTECTION PVT. LTD.
DATASHEET

COMPATIBLE DEVICES

C-100PD	Smoke Detector
C-100HD	Heat Detector
C-100PHD	Multi Criteria Detector
C-100MM	MS MCP
C-100MH	MS Sounder
C-100AM	ABS MCP
C-100AH	ABS Sounder
C-100SS	ABS Sounder Strobe
C-100RM	Relay Module
RI-100	Response Indicator
C-100SB	Detector Base

ORDERING INFORMATION:

MODEL NO	PACK QTY.	DIMESION (WXHXD) MM	WEIGHT
C-132Z	1	660X410X180	16 KG